

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Stern Tube Bearing Material**

with type designation(s)  
**NORDEN CM7**

Issued to

**NORDEN MARINE BEARINGS AS**  
**Os, Norway**

is found to comply with

**DNV GL class programme DNVGL-CP-0081 – Type approval – Synthetic bearing bushing materials**  
**DNV GL rules for classification – Ships**

**Application :**

**Synthetic water lubricated propeller shaft bearing material. The Type Approval is valid only when the installation/application of the product is according to the DNV GL Rules and the Manufacturer's recommendations. Maximum nominal bearing pressure: 0.6 MPa.**

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

This Certificate is valid until **2022-09-19**.

Issued at **Høvik** on **2017-09-20**

DNV GL local station: **Bergen**

for **DNV GL**

Approval Engineer: **Gisle Hersvik**

.....  
**Martin Strande**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

## Product description

**NORDEN CM7**; An elastomeric material of thermosetting crosslinked polymer type, with added lubricants. Water lubricated non-metallic propeller shaft bush bearings, with axial grooves in the top half of the bearing, in stave in sleeve bush (cylindrical) form in single and multiple segments.

## Place of Manufacture

Norden Marine Bearings AS, Industriveien 13, N-5210, Os, Norway

## Application/Limitation

Fields of Application: - Stern Tube/Propeller Shaft Bearings  
- Propeller Shaft Bracket Bearings

Lubricants; - Water

Surface Pressure; - 0.6 MPa, maximum, for minimum length to diameter (L/D) ratio of 2:1 for the bearing next to propeller. For all the other positions, L/D ratio as per Manufacturer's recommendations.

Installation; - Press fit  
- Freeze fit  
- Adhesive bonded  
- Tapered keyset

Dimensions; - As per DNV GL Rules and Manufacturer's recommendations.  
- Min – max diameters (OD): 50 – 2500 mm  
- Min – max thicknesses (WT): 8 – 120 mm  
- Optimum wall thickness, Ref. Norden Marine Bearings' Engineering/Design Manual.

The Type Approval is valid only when the installation/application of the product is according to the specified DNV GL Rules and the Manufacturer's recommendations.

Any significant changes in design and/or quality of the material will render the approval invalid.

## Type Approval documentation

### Tests carried out

Type Testing has been carried out in accordance with **Type Approval documentation**.


### Marking of product

Product shall be marked with *manufacturer's name*; **Norden Marine Bearings AS, Os, Norway**, *type designation*; **NORDEN CM7**, *item number and dimensions*.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV GL Type Approval Certificate.

### Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.



Job Id:  
Certificate No: **TAM00000NW**

Periodical Assessment to be performed after 2 and 3.5 years (Certificate Retention) and at renewal after 5 years (Certificate Renewal).

The main elements of the Periodical Assessment are to:

- Ensure that **Type Approval documentation** is available.
- Review design, materials, production process, and performance with respect to possible changes, in order to ensure compliance with **Type Approval documentation** and/or referenced material specifications.
- Ensure traceability between manufacturer's product marking and DNV GL Type Approval Certificate.

END OF CERTIFICATE